


DECLARATION OF PERFORMANCE





1. Product type-10.4 N Masonry Unit

2. **Identification Code** 100 BL 10

Intended use-3. Category II Aggregate Concrete Masonry Units, internal/external

walls are to be rendered

CES Quarry Products Ltd, Dorans' Rock, 124 4. Manufacturer-

Crossgar Road, Saintfield, County Down,

Northern Ireland BT24 7JQ

5. Not Applicable Authorised Representative-

System 4 6.

BS EN 771-3: 2011 7. Harmonised Standard-Not Applicable ETA-8. 9. Declared Performance: See Table Below

ESSENTIAL CHARACTERISTICS	PERFORMANCE	Harmonised technical specification
Dimensions	440mm x 100mm x 215mm	
Dimensional Tolerances	Category D1 Flatness NPD Plane Parallelism NPD	
Configuration	Group 1 unit to EN 1996-1-1	
Compressive Strength	Declared Mean > 10.4 N/mm	
Dimensional Stability	Moisture movement < 1.5 mm/m	BS EN 771-3: 2011
Shear Bond Strength	0.15 N/mm	
Reaction to Fire	Euroclass A1	
Water Absorption	Declared value : <600g/m2m	
Water Vapour Diffusion Coefficient	Declared value : 5/15	
Direct Airborne Sound Insulation	Gross Dry Density: 2030 kg/m3 Configuration: As above	
Thermal Conductivity	Declared Value : 0.98 W/mK	
Dangerous Substances	See Note	
Release of other dangerous substances	NPD	
Durability against freeze-thaw	NPD	

NPD - No Property Declared

Material Safety Data Sheets are available on request for this product.

10. The performance of the product identified in 1 & 9 is in conformity with the declared performance in 9.

This Declaration of Performance is issued on the sole responsibility of the manufacturer identified in 4.

Signed on behalf of the manufacturer -

Ian McDougall

(Production Director)

CES Quarry Products Ltd

1st March 2015