



CES Quarry Products Ltd

Kilkeel Industrial Park, The Harbour, Kilkeel
Co. Down, N. Ireland, BT34 4AX

T. 028 4176 2707
F. 028 4176 4582
E. accounts@cesquarryproducts.com
E. sales@cesquarryproducts.com
W. www.cesquarryproducts.com

Aughrim - Dunavil - Murlough - Edendarriff - Castlenavan - Doran's Rock - Moneyreagh

Recommendations for laying



Super Screed

CES Super Screed is different from dry floor screed. The main difference is the fluidity and final strength. CES Super Screed is suitable when used in conjunction with under floor heating pipes. The consistency of super screed allows the heating pipes to be completely encapsulated making for more efficient heat transfer.

After all electrical ducting and water pipes have been laid on your sub-floor and polystyrene has been positioned on the floor, plastic must be laid over the whole floor and any joints between the plastic must be overlapped and fully taped up.

It is also recommended that 100mm of the plastic should be turned up the walls to give a tank effect. Make sure all holes between rooms and at external doors are sealed to stop Super Screed escaping.

The underfloor heating pipes can now be installed. If this procedure is not followed there is the possibility super screed could get under the polystyrene and the whole floor could float. Make sure your under floor heating pipes are well fixed to the polystyrene through the plastic, also it is essential your pipes are tested and left full of water.

There is the possibility of air bubbles appearing on the finished super screed floor. Also because of the high moisture content and the curing process a skin or flakiness may appear on the surface. This does not compromise the integrity of the floor and can be scraped off after curing if necessary. Super screed is pumped into your house and only takes a few hours to complete instead of days using the conventional dry floor screed. Curing time for super screed is similar to dry screed but if tiles or timber flooring are being fixed to the screed the moisture content may need to be monitored by your finished floor layer to ensure the correct quality of adhesion, as is normal with any floor.

For Information on all our products and services please call

0845 60 43 300

Alternatively visit our web site at

www.cesquarryproducts.com



Super Screed

CES Super Screed Supply & Lay Team Picture Guide



Floor Must be 'Tanked'



Technical



Pump



Flow



Supply & Lay



Excellent Finish

For information on all our products and services please call

0845 60 43 300

Alternatively visit our web site at

www.cesquarryproducts.com

HEALTH & SAFETY WARNING

As CES products contain cement which can be harmful, please take care when using our products.

In the event of an accident please seek medical attention immediately.

Always wear the relevant PPE gear when working with our products.