



Concrete Blocks

CES Quarry Products Ltd have been manufacturing concrete blocks since the 1950's when it was an 8 man manual operation making 6 blocks at a time, producing just over 3000 number blocks per day!



For a quotation please call
028 9751 9494



CES Quarry Products Ltd.

Doran's Rock, 124 Crossgar Road, Saintfield, Co. Down, BT24 7JQ
Tel: 028 9751 9494 All sales enquiries: sales@cesquarryproducts.com



www.cesquarryproducts.com



CES Concrete Blocks



CES Quarry Products Ltd have been manufacturing concrete blocks since the 1950's when it was an 8 man manual operation making 6 blocks at a time, producing just over 3000 number blocks per day! As with all parts of our business we evolved firstly to producing 12 blocks at a time then to 16, until what it is now the industry standard 44. We were one of the first companies to purchase the Finlay 44 block maker which allowed us to increase our production to 40,000 blocks per day with a 3 man production team, of which one has been at the helm of production for almost 30 years! This is why we are one of the market leaders in the Greater Belfast area and beyond, through quality of product and quality of service. At CES our customers are not just account numbers, they are part of our growing family!

Why use CES Concrete Blocks?

- Manufactured to BS EN771-3
- Undergo daily internal testing by our experienced staff
- Undergo weekly external testing by CTS Antrim
- 100% recyclable
- Knowledgeable and helpful staff
- Over 60 years experience of production
- Reliable and timely deliveries
- Consistency of product and service
- The personal approach



Size (mm)	440x215	440x215	440x300	350x300	440x140	440x100	215x65
Thickness (mm)	100	140	100	100	100	100	100
Size (to nearest inch)	18x9x4	18x9x6	18x12x4	14x12x4	18x6x4	18x4x4	9x2.5x4
Density 7n (kg/m ³)	1950	1950	1950	1950	1950	1950	1950
Avg Weight (kg)	18.5	26	25.8	20.5	12	8.4	2.8
Strengths Available	7n, 10n & 15n*	7n, 10n & 15n*	7n & 10n*	7n & 10n*	7n, 10n & 15n*	7n, 10n & 15n*	15n
Int Thermal Conductivity (W/mK)	1.32	1.32	1.32	1.32	1.32	1.32	1.32
Ent Thermal Conductivity (W/mK)	1.42	1.42	1.42	1.42	1.42	1.42	1.42
Qty/Bale (ring)	88 (44)	64 (32)	66 (33)	66 (33)	132 (66)	176 (88)	512 (128)
Sound Reduction (Db)	43	46	48	48	43	43	43
Finish	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Colour	Natural	Natural	Natural	Natural	Natural	Natural	Natural

* Not carried in stock but can be made to order.